


**alure family**  
overview

with standard configuration described  
for full list of options consult submittal sheets

Section View	Series	Size	Mounting	Lengths	Distribution	Features
	<b>C1 alure<sup>1</sup></b>	1-7/8" h 6-1/4" w	Linear Pendant or Ceiling Mount	Various Lengths- Available in Rows	Broad Distribution Suspended or Library Ceiling Mount	This direct/indirect compliments our alure <sup>4</sup> stack mount luminaires

- T5 standard or T5HO; single or dual lamps in cross
- 60% recycled aluminum extrusion and milled end-caps
- pre-installed, single 4ft stainless steel aircraft cables and fully adjustable cable grippers with locking mechanism
- pre-installed, clear, braided power cord
- canopy kit for each mounting point
- optional surface mounting kit

	<b>C2 alure<sup>2</sup></b>	1-7/8" h 3-3/4" w	Stack Top, Surface or Cantilever Arm Mount	Various Lengths- Available in Rows	Focused Distribution Direct or Direct/Indirect	Mount under the top shelf of a library stack - row mounting allows an uninterrupted line
---	-----------------------------	----------------------	--	------------------------------------	--	--


- T5 standard or T5HO
- 60% recycled aluminum extrusion and milled end-caps
- power wired from J Box directly into fixture or cantilevered arm
- optional stack top integration or surface mount kit, or dual or single cantilevered arm kit (post height/arm length as specified)
- cantilevered arm/posts are powder coated to match luminaire

	<b>C3 alure<sup>3</sup></b>	1-7/8" h 2-3/4" w one side  2" square post	Table Mount	Various Lengths- Available in Rows	Direct	Structurally integrated table lamp – perfect for study carrels, reading & laboratory tables
--	-----------------------------	--	-------------	------------------------------------	--------	---

- T5 standard or T5HO
- 60% recycled aluminum extrusion and milled end-caps
- remote ballast box is bolted directly to table top and runs along entire length of fixture
- optional on/off switches and /or receptacles installed on ballast box
- single or dual fixtures (shown) cantilevered off a steel post (post height as specified) provides light on both sides of a desk
- posts are powder coated to match luminaire

	<b>C4 alure<sup>4</sup></b>	1-7/8" h 5" w	Cantilever Arm Mount	Various Lengths- Available in Rows	Direct or Direct/Indirect	Cantilevered arms structurally integrated into library stacks
---	-----------------------------	------------------	----------------------	------------------------------------	---------------------------	---

- T5 standard or T5HO universal
- 60% recycled aluminum extrusion and milled end caps
- power wired from inside wall or J Box directly into fixture or cantilevered arm
- dual or single cantilevered arm kit (post height/arm length as specified)
- cantilevered arm/posts are powder coated to match luminaire
- integrates into any library stack; a single cantilevered arm above an aisle lights both stack faces

	<b>C5 alure<sup>5</sup></b>	3-1/2" h 3-3/4" w 3" aperture	Recessed	Various Lengths- Available in Rows	Broad Distribution Direct	Broad distribution or focused reflector as grazing option
---	-----------------------------	-------------------------------------	----------	------------------------------------	---------------------------	---

- T5 standard or T5HO; single lamp, dual in cross or staggered
- 60% recycled aluminum extrusion and flanges
- flangeless appearance mounting for gyp ceiling or standard t-bar ceiling
- flanged appearance for wood, metal, slot grid, shadow moldings etc. ceilings using powder coated flange
- powdercoated blade baffle with grazing option