

ORDERING CODE

K1

S

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


OUTPUT	DISTRIBUTION	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
High	90/10 Slots	1943 lm/ft	19 W/ft	102 lm/W
	100% Symmetric	1658 lm/ft	19 W/ft	87 lm/W
Standard	90/10 Slots	975.5 lm/ft	9.5 W/ft	103 lm/W
	100% Symmetric	832 lm/ft	9.5 W/ft	88 lm/W

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	OUTPUT	LED CCT	CRI
BASELINE	LH	4000K	80+ CRI
	LS - 50%	3500K - 97%	90+ CRI - 80%
		3000K - 93%	

MOUNTING OPTIONS



(S) Aircraft Cable

K1	LENGTH	OUTPUT	LED CCT	VOLTAGE	INDIRECT / DIRECT DISTRIBUTION
K1	4 Nominal 4' 8 Nominal 8' 12 Nominal 12' R_ Nominal length 16' and over*	LS LED Standard Output LH LED High Output C_ LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V	N 100% Indirect, No Slots 9 90/10 Distribution Slots*
	*Specify lengths in 4' increments	*Available from 25% to 125% of LED High Output			*"arcus" lens used with distribution slots

S	FINISH	DIMMING	EMERGENCY	OPTIONS
S Single Aircraft Cable* <small>*Standard 48" field adjustable cable, specify length to nearest inch if over 48". Black power cord provided for satin black and a-lightanium finish and white power cord provided for all other fixture finishes, unless otherwise specified.</small>	T a-lightanium™ W Satin White B Satin Black	D Standard 0-10 Dimming* D1 Lutron Eco H series (LDE1) <small>*Dimming to 1% stated for standard 0-10v dimming</small>	E1 Emergency - battery* <small>*(1) ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures < 4' length. Not available for 347V.</small>	N New York City Code