

ORDERING CODE

<b>M1</b>	
<b>8</b>	<b>Y</b>

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


OUTPUT	DISTRIBUTION	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
<b>High</b>	<b>85/15 Slots</b>	<b>2009 lm/ft</b>	<b>19 W/ft</b>	<b>106 lm/W</b>
<b>Standard</b>	<b>85/15 Slots</b>	<b>1008.75 lm/ft</b>	<b>9.5 W/ft</b>	<b>106 lm/W</b>

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

BASELINE	OUTPUT	LED CCT	CRI
	<b>LH</b>	<b>4000K</b>	<b>80+ CRI</b>
	<b>LS - 50%</b>	<b>3500K - 97%</b>	<b>90+ CRI - 80%</b>
		<b>3000K - 93%</b>	

MOUNTING OPTIONS



M1					<b>8</b>
SERIES	LENGTH	OUTPUT	LED CCT	VOLTAGE	INDIRECT / DIRECT DISTRIBUTION
M1	<b>4</b> Nominal 4' <b>8</b> Nominal 8' <b>12</b> Nominal 12' <b>R_</b> Nominal length 16' and over* <small>*Specify lengths in 4' increments</small>	<b>LS</b> LED Standard Output <b>LH</b> LED High Output <b>C_</b> LED Custom Output* <small>*Available from 25% to 125% of LED High Output</small>	<b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>U</b> Universal 120V - 277V <b>3</b> 347V	<b>8</b> 85/15 Distribution Slots* <small>*"arcus" lens used with distribution slots</small>

<b>Y</b>				
MOUNTING	FINISH	DIMMING	EMERGENCY	OPTIONS
<b>Y</b> Yoke Cable	<b>T</b> a·lightanium™ <b>W</b> Satin White <b>B</b> Satin Black	<b>D</b> Standard 0-10 Dimming* <b>D1</b> Lutron Eco H series (LDE1) <small>*Dimming to 1% stated for standard 0-10v dimming</small>	<b>E1</b> Emergency - battery* <small>*(1) ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures &lt; 4' length. Not available for 347V.</small>	<b>N</b> New York City Code <b>V</b> Deco Endcap