

ORDERING CODE

M1

8 **Y**

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


OUTPUT	DISTRIBUTION	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
High	85/15 Slots	2009 lm/ft	19 W/ft	106 lm/W
Standard	85/15 Slots	1008.75 lm/ft	9.5 W/ft	106 lm/W

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

BASELINE	OUTPUT	LED CCT	CRI
	LH	4000K	80+ CRI
	LS - 50%	3500K - 97%	90+ CRI - 80%
		3000K - 93%	

MOUNTING OPTIONS



M1	LENGTH	OUTPUT	LED CCT	VOLTAGE	8
SERIES	LENGTH	OUTPUT	LED CCT	VOLTAGE	INDIRECT / DIRECT DISTRIBUTION
M1	4 Nominal 4' 8 Nominal 8' 12 Nominal 12' R_ Nominal length 16' and over*	LS LED Standard Output LH LED High Output C_ LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V	8 85/15 Distribution Slots*
	*Specify lengths in 4' increments	*Available from 25% to 125% of LED High Output			*"arcus" lens used with distribution slots

Y	FINISH	DIMMING	EMERGENCY	OPTIONS
MOUNTING	FINISH	DIMMING	EMERGENCY	OPTIONS
Y Yoke Cable	T a·lightanium™ W Satin White B Satin Black	D Standard 0-10 Dimming* D1 HiLume Ecosystems 1% (LDE1)	E1 Emergency - battery*	N New York City Code V Deco Endcap
		*Dimming to 1% stated for standard 0-10v dimming	*(1) ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures < 4' length. Not available for 347V.	