

ORDERING CODE

**P1**

**N** **L**

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
OUTPUT			
<b>High</b>	<b>981 lm/ft</b>	<b>9.5 W/ft</b>	<b>103 lm/W</b>
<b>Standard</b>	<b>592.5 lm/ft</b>	<b>5 W/ft</b>	<b>125 lm/W</b>

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	OUTPUT	LED CCT	CRI
BASELINE	<b>LH</b>	<b>4000K</b>	<b>80+ CRI</b>
	<b>LS - 50%</b>	<b>3500K - 97%</b>	<b>90+ CRI - 80%</b>
		<b>3000K - 93%</b>	

MOUNTING OPTIONS



(N) | Surface Mount

P1					
SERIES	LENGTH	OUTPUT	LED CCT	VOLTAGE	INDIRECT DISTRIBUTION
P1	<b>2</b> Nominal 2' <b>3</b> Nominal 3' <b>4</b> Nominal 4'	<b>LS</b> LED Standard Output <b>LH</b> LED High Output <b>C_</b> LED Custom Output*	<b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>U</b> Universal 120V - 277V <b>3</b> 347V	<b>O</b> Open / No Reflector <b>M</b> Symmetric <b>N1</b> Standard Asymmetric <b>N2</b> Asymmetric Sidethrow
<small>Contact factory for fluorescent options (i.e. ILH + DLS)                      *Available from 25% to 125% of LED High Output</small>					

N	L		
MOUNTING	FINISH	DIMMING	OPTIONS
<b>N</b> Surface Mount	<b>L</b> Gloss White	<b>D</b> Standard 0-10 Dimming <b>D1</b> Lutron Eco H series (LDE1)	<b>N</b> New York City Code <b>CRI</b> 90+ CRI
<small>Dimming to 1%, see technical section</small>			