

ORDERING CODE

P2

N **L**

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
OUTPUT			
High	981 lm/ft	9.5 W/ft	103 lm/W
Standard	592.5 lm/ft	5 W/ft	125 lm/W

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	OUTPUT	LED CCT	CRI
BASELINE	LH	4000K	80+ CRI
	LS - 50%	3500K - 97%	90+ CRI - 80%
		3000K - 93%	

MOUNTING OPTIONS



(N) | Surface Mount

SERIES	LENGTH	OUTPUT	LED CCT	VOLTAGE	INDIRECT DISTRIBUTION
P2	2 Nominal 2' 3 Nominal 3' 4 Nominal 4'	LS LED Standard Output LH LED High Output C_ LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V	O Open / No Reflector M Symmetric N1 Standard Asymmetric N2 Asymmetric Sidethrow
<small>Contact factory for fluorescent options (i.e. ILH + DLS) *Available from 25% to 125% of LED High Output</small>					

N	L		
MOUNTING	FINISH	DIMMING	OPTIONS
N Surface Mount	L Gloss White	D Standard 0-10 Dimming D1 HiLume Ecosystems 1% (LDE1)	N New York City Code CRI 90+ CRI
<small>Dimming to 1%, see technical section</small>			