

ORDERING CODE

**X3**

**H**

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
OUTPUT			
<b>High</b>	<b>360 lm/ft</b>	<b>9.5 W/ft</b>	<b>38 lm/W</b>
<b>Standard</b>	<b>180 lm/ft</b>	<b>5 W/ft</b>	<b>38 lm/W</b>
<b>Low</b>	<b>90 lm/ft</b>	<b>2.5 W/ft</b>	<b>38 lm/W</b>

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	OUTPUT	LED CCT	CRI
BASELINE	<b>LH</b>	<b>4000K</b>	<b>80+ CRI</b>
	<b>LS - 50%</b>	<b>3500K - 97%</b>	<b>90+ CRI - 80%</b>
	<b>LL - 25%</b>	<b>3000K - 93%</b>	

MOUNTING OPTIONS



X3							H
SERIES	VERTICAL	CANTILEVER	OUTPUT	LED CCT	VOLTAGE	OPTICS	
X3	<b>8</b> Nominal 8' <b>9</b> Nominal 9' <b>10</b> Nominal 10' <b>11</b> Nominal 11' <b>U_</b> Unlit*	<b>2</b> Nominal 2' <b>3</b> Nominal 3' <b>0</b> No Cantilever	<b>LL</b> LED Low Output <b>LS</b> LED Standard Output <b>LH</b> LED High Output <b>C_</b> LED Custom Output*	<b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>U</b> Universal 120V - 277V <b>3</b> 347V	<b>H</b> HTD-UV	
	*Specify height, max 15'	*Cantilever arm at 90 degree angle from vertical	*Available from 25% to 125% of LED High Output				

MOUNTING	FINISH	DIMMING	OPTIONS
<b>M</b> Chamfered Base <b>S</b> Square Base <b>DR</b> Direct Burial*	<b>T</b> a·lightanium™ <b>B</b> Satin Black <b>DB</b> Dark Bronze <b>O_</b> Other*	<b>D</b> Standard 0-10 Dimming*	<b>N</b> New York City Code
*Reduces above ground height up to 4" once backfilled	*Specify RAL#	*Dimming to 1% stated for standard 0-10v dimming	