



ORDERING CODE

X4

H **F**

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K

	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
OUTPUT			
High	360 lm/ft	9.5 W/ft	38 lm/W
Standard	180 lm/ft	5 W/ft	38 lm/W
Low	90 lm/ft	2.5 W/ft	38 lm/W

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	OUTPUT	LED CCT	CRI
BASELINE	LH	4000K	80+ CRI
	LS - 50%	3500K - 97%	90+ CRI - 80%
	LL - 25%	3000K - 93%	

MOUNTING OPTIONS



(F) | Wall Mount with Backplate

X4					H	F
SERIES	LENGTH	OUTPUT	LED CCT	VOLTAGE	OPTICS	MOUNTING
X4	2 Nominal 2' 3 Nominal 3' 4 Nominal 4'	LL LED Low Output LS LED Standard Output LH LED High Output C_ LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V	H HTD-UV	F Wall Mount with Backplate
*Available from 25% to 125% of LED High Output						

FINISH	DIMMING	OPTIONS
T a·lightanium™ B Satin Black DB Dark Bronze O_ Other*	D Standard 0-10 Dimming*	N New York City Code MRL_ 2" LED Downlight Module*
*Specify RAL#	*Dimming to 1% stated for standard 0-10v dimming	Up/Down combination only. LED modules are on a separate circuit from linear section of the fixture.

LED MODULE	WATTAGE	CCT	BEAM ANGLE
	4 4W 8 8W	30 3000K 40 4000K	17 17° Total Beam Angle