

ORDERING CODE

<b>X7</b>	<b>3</b>	<b>6</b>
<b>G</b>		

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
OUTPUT			
<b>Standard</b>	<b>310 lm/ft</b>	<b>5 W/ft</b>	<b>62 lm/W</b>
<b>Low</b>	<b>155 lm/ft</b>	<b>2.5 W/ft</b>	<b>62 lm/W</b>

Custom tuned output available from 50% to 200% of standard output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	OUTPUT	LED CCT	CRI
BASELINE	<b>LS</b>	<b>4000K</b>	<b>80+ CRI</b>
	<b>LL - 50%</b>	<b>3500K - 97%</b>	<b>90+ CRI - 80%</b>
		<b>3000K - 93%</b>	

MOUNTING OPTIONS



X7	3	6				G
SERIES	HEIGHT	CANTILEVER	OUTPUT	LED CCT	VOLTAGE	OPTICS
X7	3 Nominal 3'	6 Nominal 6"	<b>LL</b> LED Low Output <b>LS</b> LED Standard Output <b>C_</b> LED Custom Output*	<b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>U</b> Universal 120V - 277V <b>3</b> 347V	<b>G</b> Clear Glass
*Available from 25% to 125% of LED High Output						

MOUNTING	FINISH	DIMMING	OPTIONS
<b>M</b> Chamfered Base <b>S</b> Square Base <b>DR</b> Direct Burial*	<b>T</b> a·lightanium™ <b>B</b> Satin Black <b>DB</b> Dark Bronze <b>O_</b> Other*	<b>D</b> Standard 0-10 Dimming*	<b>N</b> New York City Code
<small>*Reduces above ground height up to 4" once backfilled</small>	<small>*Specify RAL#</small>	<small>*Dimming to 1% stated for standard 0-10v dimming</small>	