

ORDERING CODE

ABS
R

H

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
OUTPUT			
High	973 lm/ft	9.5 W/ft	102 lm/W
Standard	486.5 lm/ft	5 W/ft	102 lm/W

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	OUTPUT	LED CCT	CRI
BASELINE	LH	4000K	80+ CRI
	LS - 50%	3500K - 97%	90+ CRI - 80%
		3000K - 93%	

MOUNTING OPTIONS



(R) | Direct Wall Mount

ABS					H
SERIES	LENGTH OR PATTERN TYPE	OUTPUT	LED CCT	VOLTAGE	INDIRECT OPTICS
ABS	_ Nominal Length* M_ Exact Length** PL_X_ "L" Shape*** PU_X_ "U" Shape*** PR_X_ Rectangle / Square*** <small>*Specify in feet to the nearest foot (i.e. 12) **Specify in inches to then nearest 1/8 (i.e. M180.125) ***Specify in inches to the nearest 1/8 (See Pattern Guide for details)</small>	LS LED Standard Output LH LED High Output C_ LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V	H HTD™ Lens
		<small>*Available from 25% to 125% of LED High Output</small>			

R				
MOUNTING	FINISH	DIMMING	EMERGENCY	OPTIONS
R Wall	P Primed, grey O_ Other* <small>*Specify RAL#</small>	D Standard 0-10 dimming* D1 Lutron Eco H series (LDE1) D3 Other Dimming** <small>*Dimming to 1% stated for standard 0-10v dimming **Specify model/series</small>	EC Emergency - circuited E_ Emergency - battery* <small>*Factory-installed emergency battery pack: ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures < 4' length. Not available for 347V. See technical data for more information.</small>	M Multi-Circuit* N New York City Code CRI 90+ CRI <small>*Submit multi-circuiting requirements</small>