



INSTALLATION STEPS

ATTENTION: Risk of fire and electrical shock. Fixture to be installed by qualified contractor according to local codes and ordinances. When mounting this fixture to either a gypsum or Ibar ceiling it must be supported according to local codes and ordinances to accommodate the fixtures weight and should be installed with two people.

FIXTURE SIZE	20"	32"	48"
NOMINAL FIXTURE WEIGHT	13 LBS	25 LBS	50 LBS

- 1**
- [A] - Connections: White+, Black-, Green, (if dimming is required): Purple Dim+, Grey Dim-
 - [B] - Attach mounting plate to junction box with #8-32 screws (provided by others)
 - [C] - Secure mounting plate to ceiling joists, blocking, or anchors with optional additional screws (provided by others)
 - [D] - Connect driver(s) to LED board(s). For 20" & 32" the LED array is powered by one driver and require only one connection. The 48" fixture has two drivers, and requires two connections to each half of the boards.
 - [E] - Raise the fixture towards the mounting plate allowing the plates fingers to enter the compartment on the back of the fixture, twisting into place.
 - [F] - The spring plunger on the back compartment will snap and lock into place on one of the holes on the mounting plates fingers.

- 2** Service | Fixture Dismount
[A] - Pull wire lanyard away from fixture to disengage spring lock and twist the fixture off the mounting plate.
- 3** Service | LED & Diffuser Maintenance
[A] - Remove hex screws holding brackets to ring. Note if this step is performed with the fixture in place it should be performed with two people to ensure no damage to the fixture.
[B] - Remove ring to access the diffuser.