

ORDERING CODE

<b>ATL3</b>	<b>LH</b>	<b>U</b>
	<b>D</b>	

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


OUTPUT	DIAMETER	LUMEN OUTPUT	INPUT WATTS	EFFICACY
High	20"	2,665 lm	38.3 W	70 lm/W
	32"	6,559 lm	80 W	82 lm/W
	48"	15,795 lm	183 W	86 lm/W
Standard	20"	2,025 lm	27.7 W	73 lm/W
	32"	5,241 lm	60.6 W	86 lm/W
	48"	11,520 lm	122.6 W	94 lm/W

Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	LED CCT	CRI
BASELINE	4000K	80+ CRI
	3500K - 97%	90+ CRI - 80%
	3000K - 93%	

MOUNTING OPTIONS



ATL3		LH		U	
SERIES	DIAMETER	OUTPUT	LED CCT	VOLTAGE	MOUNTING
ATL3	20 20" 32 32" 48 48"	LH LED High Output LS LED Standard Output C_ LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V	S Aircraft Cable* F Ceiling / Surface Mount P_ Rigid Stem** P_V_ Swivel Stem**
		*Contact Design Assist for custom tuning			
		*Black power cord provided for satin black and a-lighttanium finish, unless otherwise specified. White power cord provided for satin white finish, unless otherwise specified. **Indicate stem length. 1.00" - 36.00". Use of swivel stem highly recommended.			

	D	
FINISH	DIMMING	EMERGENCY
T a-lighttanium™ W Satin White B Satin Black O_ Other*	D Standard 0-10 dimming*	E1 Emergency - battery*
*Specify RAL#	*Dimming to 1% stated for standard 0-10v dimming **Specify model/series	*(1) ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures <4' length. Not available for 347V. 20' available with remote emergency driver.