



ORDERING CODE

ATL6	20	LH	U
W	D		

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K

OUTPUT	DIAMETER	LUMEN OUTPUT	INPUT WATTS	EFFICACY
High	20"	2,665 lm	38.3 W	70 lm/W
Standard	20"	2,025 lm	27.7 W	73 lm/W

Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	LED CCT	CRI
BASELINE	4000K	80+ CRI
	3500K - 97%	90+ CRI - 80%
	3000K - 93%	

MOUNTING OPTIONS



(T/X) | T-Bar 9/16" / T-Bar 15/16"

ATL6	20	LH		U	
SERIES	DIAMETER	OUTPUT	LED CCT	VOLTAGE	MOUNTING
ATL6	20 20"	LH LED High Output LS LED Standard Output C_ LED Custom Output	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V	T T-Bar 9/16" X T-Bar 15/16"
*Contact Design Assist for custom tuning					

W	D	
FINISH	DIMMING	EMERGENCY
W Textured White	D Standard 0-10 dimming*	E1 Emergency - battery*
*Dimming to 5% stated for standard 0-10v dimming **Specify model/series		*(1) IOTA-ILB-CP12-B (12W unit, integral). Specify desired quantity of batteries. Not available for 347V, 20" remotely mounted in RME1 enclosure.