



ORDERING CODE

ATL5	LH	U	G
W	D		

PROJECT INFO

DATE

TYPE

QUANTITY

PERFORMANCE AT 4000K


OUTPUT	DIAMETER	LUMEN OUTPUT	INPUT WATTS	EFFICACY
High	20"	2,665 lm	38.3 W	70 lm/W
	32"	6,559 lm	80 W	82 lm/W
	48"	15,795 lm	183 W	86 lm/W
Standard	20"	2,025 lm	27.7 W	73 lm/W
	32"	5,241 lm	60.6 W	86 lm/W
	48"	11,520 lm	122.6 W	94 lm/W

Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	LED CCT	CRI
BASELINE	4000K	80+ CRI
	3500K - 97%	90+ CRI - 80%
	3000K - 93%	

MOUNTING OPTIONS



ATL5		LH		U	G
SERIES	DIAMETER	OUTPUT	LED CCT	VOLTAGE	MOUNTING
ATL5	20 20" 32 32" 48 48"	LH LED High Output LS LED Standard Output C_ LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V	G Flush Gyp
*Contact Design Assist for custom tuning					

W	D	
FINISH	DIMMING	EMERGENCY
W Textured White	D Standard 0-10 dimming*	E1 Emergency - battery*
*Dimming to 5% stated for standard 0-10v dimming **Specify model/series		*20" and 48" IOTA-ILB-CP12-B (12W unit, integral) 32" IOTA-ILB-CP05-B (5W unit, integral). Specify desired quantity of batteries. Not available for 347V. 20" remotely mounted in RME1 enclosure.