

ORDERING CODE

**C2**

**S** **F**

PROJECT INFO

TYPE

DATE

QUANTITY

LIGHT LOSS FACTORS


	OUTPUT	LED CCT	CRI
BASELINE	LH	4000K	80+ CRI
	LS - 50%	3500K - 97%	90+ CRI - 80%
		3000K - 93%	

PERFORMANCE AT 4000K

	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
OUTPUT			
High	758 lm/ft	9.5 W/ft	80 lm/W
Standard	379 lm/ft	5 W/ft	80 lm/W

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

MOUNTING OPTIONS



(F) | Surface / Top Mount

C2					S	F
SERIES	LENGTH	OUTPUT	LED CCT	VOLTAGE	DIRECT OPTICS	MOUNTING
C2	_ Nominal Length* M_ Exact Length**	LS LED Standard Output LH LED High Output C_ LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V	S WISP™ Lens	F Surface / Top Mount
<small>*Specify in feet to the nearest foot (i.e. 12)                      **Specify in inches to then nearest 1/8 (i.e. M180.125)</small>		<small>*Available from 25% to 125% of LED High Output</small>				

FINISH	DIMMING	EMERGENCY	SENSORS	OPTIONS
T a·lightanium™ W Satin White B Satin Black O_ Other*	D Standard 0-10 dimming* D1 HiLume Ecosystems 1% (LDE1) D3 Other Dimming**	EC Emergency - circuited E_ Emergency - battery*	O Occupancy Sensor* P Photocell / Daylight Sensor** OP Occupancy & Daylight Sensor	M Multi-Circuit* N New York City Code
<small>*Specify RAL#</small>	<small>*Dimming to 1% stated for standard 0-10v dimming                      **Specify model/series</small>	<small>*Factory-installed emergency battery pack: ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures &lt; 4' length. Not available for 347V. See technical data for more information.</small>	<small>*Wattstopper FS-205 (Ø1")                      **Wattstopper FD-301 wired for daylight harvesting. Requires 0-10v dimming.</small>	<small>*Submit multi-circuiting requirements</small>