

ORDERING CODE

ARL2

LG S

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


| | NOMINAL LUMEN OUTPUT | INPUT WATTS | EFFICACY |
|----------|----------------------|-------------|----------|
| OUTPUT | | | |
| High | 1,097 lm/ft | 12.7 W/ft | 87 lm/W |
| Standard | 548.5 lm/ft | 6.3 W/ft | 87 lm/W |

Custom tuned output available from 25% to 100% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

| | OUTPUT | LED CCT | CRI |
|----------|----------|-------------|---------------|
| BASELINE | LH | 4000K | 80+ CRI |
| | LS - 50% | 3500K - 97% | 90+ CRI - 80% |
| | | 3000K - 93% | |

MOUNTING OPTIONS



| ARL2 | | | | | LG |
|--------|---|---|---|---|---------------------------|
| SERIES | LENGTH OR PATTERN TYPE | OUTPUT | LED CCT | VOLTAGE | OPTICS |
| ARL2 | 2 Nominal 2' 4 Nominal 4' 6 Nominal 6' 8 Nominal 8' _ Nominal length* CP Custom Pattern** | LS LED Standard Output LH LED High Output C_ LED Custom Output | 30 3000K 35 3500K 40 4000K | U Universal 120V - 277V 3 347V | LG 3-D Light Guide |
| | <small>*Specify in increments of 4' lengths **Contact Design Assist</small> | <small>*Available from 25% to 100% of LED High Output</small> | | | |

| S | | | | |
|--|--|---|--|---|
| MOUNTING | FINISH | DIMMING | EMERGENCY | SENSORS |
| S Aircraft Cable* <small>*Standard 48" field adjustable cable, specify length to nearest inch if over 48". Black power cord provided for satin black and a-lightanium finish and white power cord provided for all other fixture finishes, unless otherwise specified.</small> | T a-lightanium™ W Satin White B Satin Black O_ Other* <small>*Specify RAL#</small> | D Standard 0-10 dimming* D1 Lutron Eco H series (LDE1) D3_ Other Dimming** <small>*Dimming to 1% stated for standard 0-10v dimming **Specify model/series</small> | EC Emergency - circuited E_ Emergency - battery* <small>*Factory-installed emergency battery pack: ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures < 4' length. Not available for 347V. See technical data for more information.</small> | O Occupancy Sensor* P Photocell / Daylight Sensor** OP Occupancy & Daylight Sensor <small>*Wattstopper FS-205 (Ø1") **Wattstopper FD-301 wired for daylight harvesting. Requires 0-10v dimming.</small> |

| OPTIONS |
|--|
| M Multi-Circuit* N New York City Code CRI 90+ CRI <small>*Submit multi-circuiting requirements</small> |