

ORDERING CODE

<b>ARL3</b>	
<b>LG</b>	<b>S</b>

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K


	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
OUTPUT			
<b>High</b>	<b>1,097 lm/ft</b>	<b>12.7 W/ft</b>	<b>87 lm/W</b>
<b>Standard</b>	<b>548.5 lm/ft</b>	<b>6.3 W/ft</b>	<b>87 lm/W</b>

Custom tuned output available from 25% to 100% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

	OUTPUT	LED CCT	CRI
BASILINE	<b>LH</b>	<b>4000K</b>	<b>80+ CRI</b>
	<b>LS - 50%</b>	<b>3500K - 97%</b>	<b>90+ CRI - 80%</b>
		<b>3000K - 93%</b>	

MOUNTING OPTIONS



ARL3					LG
SERIES	LENGTH OR PATTERN TYPE	OUTPUT	LED CCT	VOLTAGE	OPTICS
ARL3	<b>2</b> Nominal 2' <b>4</b> Nominal 4' <b>6</b> Nominal 6' <b>8</b> Nominal 8' _ Nominal length*  <b>CP</b> Custom Pattern**	<b>LS</b> LED Standard Output <b>LH</b> LED High Output <b>C_</b> LED Custom Output	<b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>U</b> Universal 120V - 277V <b>3</b> 347V	<b>LG</b> 3-D Light Guide
	<small>*Specify in increments of 4' lengths **Contact Design Assist</small>	<small>*Available from 25% to 100% of LED High Output</small>			

S				
MOUNTING	FINISH	DIMMING	EMERGENCY	SENSORS
<b>S</b> Aircraft Cable*  <small>*Standard 48" field adjustable cable, specify length to nearest inch if over 48". Black power cord provided for satin black and a-lightanium finish and white power cord provided for all other fixture finishes, unless otherwise specified.</small>	<b>T</b> a-lightanium™ <b>W</b> Satin White <b>B</b> Satin Black <b>O_</b> Other*  <small>*Specify RAL#</small>	<b>D</b> Standard 0-10 dimming* <b>D1</b> Lutron Eco H series (LDE1) <b>D3_</b> Other Dimming**  <small>*Dimming to 1% stated for standard 0-10v dimming **Specify model/series</small>	<b>EC</b> Emergency - circuited <b>E_</b> Emergency - battery*  <small>*Factory-installed emergency battery pack: ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures &lt; 4' length. Not available for 347V. See technical data for more information.</small>	<b>O</b> Occupancy Sensor* <b>P</b> Photocell / Daylight Sensor** <b>OP</b> Occupancy & Daylight Sensor  <small>*Wattstopper FS-205 (Ø1") **Wattstopper FD-301 wired for daylight harvesting. Requires 0-10v dimming.</small>

OPTIONS
<b>M</b> Multi-Circuit* <b>N</b> New York City Code <b>CRI</b> 90+ CRI  <small>*Submit multi-circuiting requirements</small>