

ORDERING CODE

AIR2
S

PROJECT INFO

TYPE

DATE

QUANTITY


PERFORMANCE AT 4000K

OUTPUT	DIAMETER	LUMEN OUTPUT	INPUT WATTS	EFFICACY
High	Ø24"	5,935 lm	54.1 W	110 lm/W
	Ø36"	8,550 lm	76.9 W	111 lm/W
Standard	Ø24"	3,225 lm	27.3 W	118 lm/W
	Ø36"	5,295 lm	43.5 W	122 lm/W

LIGHT LOSS FACTORS

CRI	LED CCT	FACTOR
80+ CRI	4000K	BASELINE
80+ CRI	3500K	99%
80+ CRI	3000K	95%
90+ CRI	4000K	83%
90+ CRI	3500K	83%
90+ CRI	3000K	84%

MOUNTING OPTIONS



Custom tuned output available from 25% to 125% of high output.
Please consult factory for custom lumen output and wattage.

AIR2	DIAMETER	OUTPUT	LED CCT	VOLTAGE	S
SERIES					MOUNTING
AIR2	24 Ø24" 36 Ø36"	LS LED Standard Output LH LED High Output	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V Driver	S Aircraft Cable*

* Standard 48" field adjustable cable, specify length to nearest inch, if over 48". Black power cord provided for satin black and ailightanium finish, unless otherwise specified. White power cord provided for satin white finish, unless otherwise specified. Canopy is standard white finish, unless otherwise specified.

EXTERIOR FINISH	INTERIOR FINISH	DIMMING
T ailightanium™ W Satin White B Satin Black O Other*	W Satin White* O Other**	D Standard 0-10 dimming D1 HiLume Ecosystems 1% (LED1)

* Standard Color. No need specification.
**Specify RAL# Custom interior finish will affect light distribution, output and light color
*Specify RAL#

