



PERFORMANCE AT 4000K

	OUTPUT	DISTRIBUTION	NOMINAL OUTPUT	INPUT WATTS	EFFICACY
INDIRECT	High (LH)	Symmetric Wide	673 lm/ft	9 W/ft	75 lm/W
		Symmetric	912 lm/ft	9.6 W/ft	95 lm/W
		Asymmetric	670 lm/ft	9.6 W/ft	70 lm/W
	Standard (LS)	Symmetric Wide	352.5 lm/ft	5 W/ft	74 lm/W
		Symmetric	456 lm/ft	5 W/ft	95 lm/W
		Asymmetric	335 lm/ft	5 W/ft	70 lm/W

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

ORDERING CODE

**ABV1**

**D F S**

PROJECT INFO

TYPE

DATE

QUANTITY

LIGHT LOSS FACTORS

CRI	CCT	FACTOR
80+	4000K	Baseline
80+	3500K	99%
80+	3000K	95%
90+	4000K	83%
90+	3500K	83%
90+	3000K	84%

Factors above for high output (LH). For standard output (LS) -50%.

MOUNTING OPTIONS



(S) Aircraft Cable

ABV1	LENGTH	OUTPUT	LED CCT	VOLTAGE	INDIRECT DISTRIBUTION	D
ABV1	Nominal	LS Indirect LED Standard Output LH Indirect LED High Output C_ Indirect LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V	M Symmetric Wide G Symmetric N Asymmetric	D Rigid Diffuse Dust Cover

\*Specify feet in increments of 2' (i.e. 2, 4, 6...)

\*Available from 25% to 125% of LED High Output

F	HEIGHT	S	END CAP	FIXTURE FINISH	ACOUSTIC PANELS FINISH
F Filler Panel	1 12 inches 2 24 inches	S Aircraft Cable*	A Aluminum* F Acoustic Material**	T a•lightanium™ W Satin White B Satin Black O_ Other*	CG Charcoal Gray SG Silver Gray NB Navy Blue O_ Other*

\*Standard 48" field adjustable cable, specify length to nearest inch if over 48". Black power cord provided for satin black and a•lightanium finish and white power cord provided for all other fixture finishes, unless otherwise specified.

\*Same color as Fixture

\*\*Same color as Acoustic Panels

\*Specify RAL#

\*For non-standard colors consult with factory for details, lead-times and pricing

CIRCUITING	DIMMING	EMERGENCY	SENSORS	OPTIONS
1 Single Circuit 2 Multi-Circuit*	D Standard 0-10 dimming* D1 HiLume Ecosystems 1% (LDE-1) D3 Other Dimming**	EC Emergency - circuited E_ Emergency - battery*	O Occupancy Sensor* P Photocell / Daylight Sensor** OP Occupancy & Daylight Sensor	CRI 90+ CRI N New York City Code

\*Separate uplight and downlight circuits

\*Dimming to 1% stated for standard 0-10v dimming

\*\*Specify model/series

\*Factory-installed emergency battery pack: ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures < 4' length. Not available for 347V. See technical data for more information.

\*Wattstopper FS-205 (Ø1")

\*\*Wattstopper FD-301 wired for daylight harvesting. Requires 0-10v dimming.