



ORDERING CODE

ABV3	S	F
-------------	----------	----------

PROJECT INFO

TYPE

DATE

QUANTITY

PERFORMANCE AT 4000K

	OUTPUT	DISTRIBUTION	NOMINAL OUTPUT	INPUT WATTS	EFFICACY
DIRECT	High (LH)	HE Tech™	921 lm/ft	9.7 W/ft	95 lm/W
	Standard (LS)	HE Tech™	460 lm/ft	5 W/ft	95 lm/W

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

CRI	CCT	FACTOR
80+	4000K	Baseline
80+	3500K	99%
80+	3000K	95%
90+	4000K	83%
90+	3500K	83%
90+	3000K	84%

Factors above for high output (LH). For standard output (LS) -50%.

MOUNTING OPTIONS



(S) Aircraft Cable

ABV3	LENGTH	OUTPUT	LED CCT	VOLTAGE	F
SERIES	LENGTH	OUTPUT	LED CCT	VOLTAGE	INDIRECT OPTICS
ABV3	— Nominal	LS Direct LED Standard Output LH Direct LED High Output C_ Direct LED Custom Output*	30 3000K 35 3500K 40 4000K	U Universal 120V - 277V 3 347V	F Filler Panel

*Specify feet in increments of 2' (i.e. 2, 4, 6...)

*Available from 25% to 125% of LED High Output

DIRECT OPTICS	HEIGHT	S MOUNTING	END CAP	FIXTURE FINISH	ACOUSTIC PANELS FINISH
HE HE Tech™ 55 Apex Baffle 55 Degree 22 Apex Baffle 22 Degree	1 12 inches 2 24 inches	S Aircraft Cable*	A Aluminum* F Acoustic Material**	T a•lightanium™ W Satin White B Satin Black O_ Other*	CG Charcoal Gray SG Silver Gray NB Navy Blue O_ Other*

*Standard 48" field adjustable cable, specify length to nearest inch if over 48". Black power cord provided for satin black and a•lightanium finish and white power cord provided for all other fixture finishes, unless otherwise specified.

*Same color as Fixture
**Same color as Acoustic Panels

*Specify RAL#

*For non-standard colors consult with factory for details, lead-times and pricing

CIRCUITING	DIMMING	EMERGENCY	SENSORS	OPTIONS
1 Single Circuit 2 Multi-Circuit*	D Standard 0-10 dimming* D1 HiLume Ecosystems 1% (LDE-1) D3 Other Dimming**	EC Emergency - circuited E_ Emergency - battery*	O Occupancy Sensor* P Photocell / Daylight Sensor** OP Occupancy & Daylight Sensor	CRI 90+ CRI N New York City Code

*Separate uplight and downlight circuits

*Dimming to 1% stated for standard 0-10v dimming
**Specify model/series

*Factory-installed emergency battery pack: ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures < 4' length. Not available for 347V. See technical data for more information.

*Wattstopper FS-205 (Ø1")
**Wattstopper FD-301 wired for daylight harvesting. Requires 0-10v dimming.