

ORDERING CODE

**ABH3**

**F**

**HE**

**S**

PROJECT INFO

DATE

TYPE

QUANTITY

PERFORMANCE AT 4000K


	OUTPUT	DISTRIBUTION	NOMINAL OUTPUT	INPUT WATTS	EFFICACY
<b>DIRECT</b>	<b>High (LH)</b>	<b>HE Tech™</b>	<b>921 lm/ft</b>	<b>9.7 W/ft</b>	<b>95 lm/W</b>
	<b>Standard (LS)</b>	<b>HE Tech™</b>	<b>460.5 lm/ft</b>	<b>5 W/ft</b>	<b>95 lm/W</b>

Custom tuned output available from 25% to 125% of high output. Please consult factory for custom lumen output and wattage.

LIGHT LOSS FACTORS

CRI	CCT	FACTOR
80+	4000K	Baseline
80+	3500K	99%
80+	3000K	95%
90+	4000K	83%
90+	3500K	83%
90+	3000K	84%

MOUNTING OPTIONS



Factors above for high output (LH).  
For standard output (LS) -50%.

ABH3	LENGTH	OUTPUT	LED CCT	VOLTAGE
ABH3	_ Nominal Length	<b>LS</b> Direct LED Standard Output <b>LH</b> Direct LED High Output <b>C_</b> Direct LED Custom Output*	<b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>U</b> Universal 120V - 277V <b>3</b> 347V

\*Specify feet in increments of 2' (i.e. 2, 4, 6 ...)

\*Available from 25% to 125% of LED High Output

F	HE	S		
INDIRECT OPTICS	DIRECT OPTICS	MOUNTING	FIXTURE FINISH	ACOUSTIC PANELS FINISH
<b>F</b> Filler Panel	<b>HE</b> HE Tech™	<b>S</b> Aircraft Cable*	<b>T</b> a·lightanium™ <b>W</b> Satin White <b>B</b> Satin Black <b>O_</b> Other*	<b>CG</b> Charcoal Gray <b>SG</b> Silver Gray <b>NB</b> Navy Blue <b>O_</b> Other*

\*Standard 48" field adjustable cable. specify length to nearest inch if over 48". Black power cord provided for satin black and arlightanium finish and white power cord provided for all other fixture finishes, unless otherwise specified.

\*Specify RAL#

\*For non-standard colors consult with factory for details, lead-times and pricing

CIRCUITING	DIMMING	EMERGENCY	SENSORS	OPTIONS
<b>1</b> Single Circuit <b>2</b> Multi-Circuit*	<b>D</b> Standard 0-10 dimming* <b>D1</b> HiLume Ecosystems 1% (LDE1) <b>D3</b> Other Dimming**	<b>EC</b> Emergency - circuited <b>E_</b> Emergency - battery*	<b>O</b> Occupancy Sensor* <b>P</b> Photocell / Daylight Sensor** <b>OP</b> Occupancy & Daylight Sensor	<b>CRI</b> 90+ CRI <b>N</b> New York City Code

\*Separate uplight and downlight circuits

\*Dimming to 1% stated for standard 0-10v dimming  
\*\*Specify model/series

\*Factory-installed emergency battery pack: ILB-SL-CP12 (1200lm for 90min). Specify desired quantity of batteries. Not available on fixtures < 4' length. Not available for 347V. See technical data for more information.

\*\*Wattstopper FS-205 (Ø1")  
\*\*\*Wattstopper FD-301 wired for daylight harvesting. Requires 0-10v dimming.